



### PERFORMANCE DATA

	RPM	MPH	GPH	MPG	RANGE*
	600	4.0	1.3	3.08	685
	1000	6.5	2.7	2.41	536
	1500	8.9	4.4	2.02	450
	2000	9.8	7.3	1.34	297
	2500	15.1	10.8	1.39	310
	3000	25.2	13.9	1.81	403
	3500	31.9	17.6	1.81	403
'	4000	37.5	23.5	1.60	355
	4500	42.3	29.7	1.42	317
	5000	47.6	37.5	1.27	282
	5500	53.0	47.9	1.11	246
	6000	56.0	51.9	1.08	240

\* Range based on 90% Fuel Capacity


### **MODEL SPECIFICATIONS**

L.O.A.	31' 2"	
Beam	9' 6"	
Hull Draft (motors up)	22"	
Hull Draft (motors down)	32"	
Fuel Capacity**	260	U.S. gal
Max. Horsepower	600	HP
Average Dry Weight (w/Twin F300s)	8,280	lbs.
Water Capacity	20	U.S. gal
Holding Tank Capacity	20	U.S. gal
Clearance w/ Hardtop***	7' 11"	
Deadrise	24°	

## YAMAHA POWER

Outboard Model	Twin F300s (V-6)	
Outboard Dry Weight	562	lbs.
Mounting Hole	#2	
Optimum Propeller	15-1/4 x 19 SWS II	

<sup>\*\*</sup>Net tank capacity. The usable fuel capacity will be affected by several factors, including EPA-required fuel system components, temperature and loading of the boat. These factors will reduce the usable fuel capacity by approximately 10%.



0 to 30mph Acceleration = 8.3 sec.

# **TEST CONDITIONS**

Full Boat Test Weight	10,155 lbs.****
Test Personnel	2
Test Date	8/22/2013
Air/Water Temperature	87°/82°

\*\*\*\*Test Weight includes 237 gal. fuel, 5 gal. water, all optional equipment, personnel, and safety gear.

Note: Data may vary due to changes in weather, elevation, options, load and bottom conditions.

Fuel data gathered with Yamaha Fuel Management System. Speed data gathered with GPS.



<sup>\*\*\*</sup>Hardtop Clearance shown does not include options which could increase this height dimension.